

DECLARATION OF PERFORMANCE

Construction Products Regulation 305/2011

No. 11000-1611

Prismatic Grade Retroreflective Sheeting:

OmniCube T-11500 Series
OmniCube T-11500 Series with OL-2000 Transparent EC Film
OmniCube T-11500 Series with 4930 Screen Ink
OmniCube T-11500 Series with 3801 Traffic Film Black
OmniCube T-11500 Series with TrafficJet Ink & Clear Overlay
OmniCube T-11500 Series with TrafficJet UV Ink & Clear Overlay



OmniCube Series is a high-quality, 12-year durable, Full Cube, microprismatic retroreflective material with a pressure sensitive adhesive. This product is intended for use on permanent or temporary highway safety devices that require robust Class 3 retroreflective performance.



Manufactured by: Avery Dennison, Reflective Solutions

Willem Einthovenstraat 11, 2342 BH
Oegstgeest, The Netherlands

902 Feehanville Rd.
Mt. Prospect, IL 60056 USA

Avery Dennison performed factory product control and product sampling per assessment and verification of constancy of performance under System 1. Silniční vývoj - ZDZ spol. s r. o. Notified Body 1388 performed initial type testing, inspection of manufacturing facilities and factory products controls under system 1. Tzus, 060-045345 issued **ETA 15/0887** dated 25/10/2017 & **ETA 18/0544** dated 15/10/2018 & **ETA 20/0687**, **ETA 20/0882** dated 18/01/2021. Anti-Dew OL1200 included in ETA's 22/0240 & 22/0241 dated 22/08/2022

Essential Characteristics		Performance	Assessment Document
Daylight Chromaticity		Per Table 3	EAD 120001-01-0106, September 2016
Luminance Factor		Per Table 3	
Coefficient of retro-reflection, Rotational Symmetry		Per Tables 4 & 5, Rotational Variation < 10%	
Impact Resistance		No Effect	
Visibility after Weathering, Natural & Accelerated Artificial	Retroreflection	80% of Initial Requirement	
	Chromaticity & Luminance Factor	Per Table 2 Below	
Adhesion		Peel < 50mm	

The performance of OmniCube Series is in conformance with declarations herein when evaluated per EAD 120001-01-0106. This declaration of performance is issued for performance clarity under the sole discretion of Avery Dennison.

Signed for on behalf of Avery Dennison by: Erika Shang, Quality Manager

Date: 16 November, 2022, Illinois, USA

Classification: Avery Dennison - Internal

Table 2: Daytime Chromaticity and Luminance Factors^A CR1

Colour		Colour Box Coordinates				Luminance Factor β
		1	2	3	4	
White	x	0,355	0,305	0,285	0,335	$\geq 0,27$
	y	0,355	0,305	0,325	0,375	
Yellow	x	0,545	0,487	0,427	0,465	$\geq 0,16$
	y	0,454	0,423	0,483	0,534	
Red	x	0,735	0,674	0,569	0,655	$\geq 0,03$
	y	0,265	0,236	0,341	0,345	
Orange	x	0,610	0,535	0,506	0,570	$\geq 0,14$
	y	0,390	0,375	0,404	0,429	
Green	x	0,007	0,248	0,177	0,026	$\geq 0,03$
	y	0,703	0,409	0,362	0,399	
Green 2 (Worboy Green)	x	0,313	0,313	0,248	0,127	$0,01 \leq \beta \leq 0,07$
	y	0,682	0,453	0,409	0,557	
Brown	x	0,455	0,523	0,479	0,558	$0,03 \leq \beta \leq 0,09$
	y	0,397	0,429	0,373	0,394	
Blue	x	0,078	0,150	0,210	0,137	$\geq 0,01$
	y	0,171	0,220	0,160	0,038	
Grey	x	0,355	0,305	0,285	0,335	$0,12 \leq \beta \leq 0,18$
	y	0,355	0,305	0,325	0,375	
Flourescent Yellow	x	0,521	0,557	0,479	0,454	$\geq 0,38$
	y	0,424	0,442	0,520	0,491	
Flourescent Orange	x	0,595	0,645	0,570	0,531	$\geq 0,20$
	y	0,351	0,355	0,429	0,414	
Flourescent Yellow/Green	x	0,387	0,460	0,438	0,376	$\geq 0,50$
	y	0,610	0,540	0,508	0,568	
Black	x	0,385	0,275	0,235	0,345	$\leq 0,03$
	y	0,355	0,250	0,290	0,395	

Notes: A – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.1.

Table 3: Daytime Chromaticity and Luminance Factors^A CR2

Colour		Colour Box Coordinates				Luminance Factor β
		1	2	3	4	
White	x	0,305	0,335	0,325	0,295	$\geq 0,27$
	y	0,315	0,345	0,355	0,325	
Yellow	x	0,494	0,470	0,513	0,545	$\geq 0,16$
	y	0,505	0,480	0,437	0,454	
Red	x	0,735	0,700	0,610	0,660	$\geq 0,03$
	y	0,265	0,250	0,340	0,340	
Orange	x	0,631	0,560	0,506	0,570	$\geq 0,14$
	y	0,369	0,360	0,404	0,429	
Green	x	0,110	0,170	0,170	0,110	$\geq 0,03$
	y	0,415	0,415	0,500	0,500	
Green 2	x	0,313	0,313	0,248	0,127	$0,01 \leq \beta \leq 0,07$
	y	0,682	0,453	0,409	0,557	
Brown	x	0,455	0,523	0,479	0,558	$0,03 \leq \beta \leq 0,09$
	y	0,397	0,429	0,373	0,394	
Blue	x	0,130	0,160	0,160	0,130	$\geq 0,01$
	y	0,090	0,090	0,140	0,140	
Black	x	0,385	0,300	0,260	0,345	$\leq 0,03$
	y	0,355	0,270	0,310	0,395	
Fluorescent Yellow	x	0,521	0,557	0,479	0,454	$\geq 0,38$
	y	0,424	0,442	0,520	0,491	
Fluorescent Orange	x	0,595	0,645	0,570	0,531	$\geq 0,20$
	y	0,351	0,355	0,429	0,414	
Fluorescent Yellow-Green	x	0,387	0,460	0,438	0,376	$\geq 0,60$
	y	0,610	0,540	0,508	0,568	

Notes: ^A – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.1.

Table 4: Coefficients of Retroreflection¹, R_A (cd/lux/m²)
(Includes ASTM 4956 Type XI and R3C-UK)

Entrance Angle (β ₁ , β ₂ =0°)	Observation Angle (α)	R _A								
		White	Yellow	Green	Red	Blue	Brown	Fluorescent Yellow-Green	Fluorescent Orange	Fluorescent Yellow
5°	0.2°	580	435	58	87	26	17	460	175	350
30°		220	165	22	33	10	7	180	66	130
5°	0.33°	300	250	35	75	17	10	270	90	180
30°		140	128	18	30	7	5	120	42	90
5°	0.5°	420	315	42	63	19	13	340	125	250
30°		150	110	15	23	7	5	120	45	90
5°	1.0°	120	90	12	18	5	4	96	36	72
30°		45	34	5	7	2	1	36	14	27

Notes: 1 – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.3 averaging ε=0° and 90° or 0°.

Table 5: Coefficients of Retroreflection², R_A (cd/lux/m²)
(Includes Belgium 3B, Spain 3ZC, Czech Rep RA3 & Slovenia RA3 Requirements)

Entrance Angle (β ₁ , β ₂ =0°)	Observation Angle (α)	R _A						
		White	Yellow	Green	Red	Blue	Fluorescent Yellow-Green	Fluorescent Yellow
5°	0.2°	430	350	45	110	25	375	350
15°		350	270	35	90	20	-	-
30°		235	190	24	60	11	200	130
40°		55	40	7	12	3	36	-
5°	0.33°	300	250	35	75	17	270	-
15°		250	200	25	65	15	-	-
30°		150	130	18	35	7	140	-
40°		30	25	4	7	2	24	-
5°	1.0°	80	65	10	20	5	70	25
15°		60	45	7	16	3.5	-	20
30°		50	40	5	13	2.5	43	13
40°		15	13	2	5	1	9	7
5°	1.5°	15	10	1.5	3	1	-	10
15°		13	9	1	2.5	0.5	-	9
30°		10	7	1	2	0.5	-	7
40°		5	3	0.5	1	-	-	3

Notes: 2 – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.3 ε=0° only.

Table 6: Specific Signing Combination Performance Declarations

Signing Component	Product Name	Colors and Product Number	Declared Retroreflective Detail
Native Sheeting	T-11500 Series	T-11500 White T-11501 Yellow T-11505 Blue T-11507 Green T-11508 Red T-11511 & W-11111 Fluorescent Yellow T-11513 Fluorescent Yellow-Green	Per Tables 4 & 5
Electronic Cuttable Overlay [#]	OL-1000 OL-2000 OL-1200 EC Film & 3801 Black	OL-2000/1000 Clear applied to White & Yellow Native Sheeting OL1200 applied to White sheeting OL-2005 Blue OL-2007 Green OL-2008 Red 3801 Black [^]	70% of Tables 4 & 5
[^] Standard Avery Dennison product code is 801, the prefix 3(801) denotes special watermark print for Germany only			
Solvent Screen Ink [#]	4930 Series	Blue Red Black	70% of Tables 4 & 5
Digital Printing Ecosolvent [#]	TrafficJet with OL-1000 or OL-2000 Clear or OL1200 Anti-Dew	Yellow Blue Green Red Red onto T-11501 Yellow (not OL1200) Brown Worboy Green (not OL-2000) Grey + OL-1000 only Black Black onto T-11501 Yellow Black onto T-11511 FI Yellow + OL2000 Black onto W-11111 FI Yellow + OL2000	70% of Tables 4 & 5
Digital Printing UV [#]	TrafficJet with OL-1000 or OL-2000 Clear or OL1200 Anti-Dew	Yellow Blue Green Red Red onto T-11501 Yellow (not OL1200) Brown Worboy Green (not OL-2000) Black Black onto T-11501 Yellow (not OL1200)	70% of Tables 4 & 5

Notes: [#] - Declared performance for components assumes application to white native sheeting unless otherwise noted.

⁺ - Declared performance is 50% of red values stated in Tables 4 & 5.