

Avery Dennison® Instructional Bulletin for OmniBrite™ WU-7000 Series Roll-up Retroreflective Film

Instructional Bulletin : # 8.02
Revision : # 1.2
Last Updated : September 2019

Health and Safety

Read bulletin on Sheeting Storage, Handling and Cleaning prior to handling and/or use.

Storage and Conditioning

Avery Dennison Reflective Sheeting should be used within one year from the date of purchase. All guarantees and warranties, expressed or implied, shall become null and void in all respects on materials stored prior to application for periods in excess of one year. WU-7000 Roll-up Retroreflective Series include a protective film which must be removed prior to fabricating the sign.

It is recommended that Avery Dennison Reflective Sheeting be stored flat in a cool, dry environment; preferably at 65°–75°F (18.3°–29.7°C) and 45%–55% relative humidity. If materials are stored in areas separated from the application or converting area, it is advisable to allow the material to acclimate to the application or converting area prior to use.

Recommended Application

Avery Dennison Roll-Up retroreflective sheeting has been designed to be used for snaps, rivet corner pockets and sewn in corner pockets. The material composition of the corner pockets and the washers should be plastic or rubber. It is recommended for the molded pockets to not have sharp corners. In addition to the portable sign stands, Cross-brace supports can be used. It needs to be ensured that the maximum distance that the cross braces bow is not more than 0.5 inches.

Avery Dennison recommends the use of Nazdar VF111 inks to assure user satisfaction and conformance with warranty requirements. Because the choice of ink series can determine the durability, transparency and sign reflectivity level, it is important that the correct series of ink be matched with the reflective sheeting used. Differing environmental conditions found in specific regions of the country may result in the ability of Avery Dennison to increase the period of ink durability and warranty for select ink colors and series. Any exceptions to the information contained below must be confirmed in writing by Avery Dennison to become binding. Please contact Avery Dennison for further information.

Complete information to the user for proper application, storage, and other requirements can be found in the Instructional Bulletin # 8.00. This information can also be obtained by directly contacting the Technical Services department of Avery Dennison

The above Avery Dennison literature provides information to the user for proper application, storage, and other requirements. Please refer to Product Data Bulletins or your local Avery Dennison Representative

for warranty information. Find the latest information on the Avery Dennison website, www.reflectives.averydennison.com. We encourage you to check our website periodically for updates.

All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its intended and other purposes.

General Performance Consideration

The durability of Roll-Up series will depend upon compliance what's recommended application procedures geographic area exposure conditions and maintenance.