

DECLARATION OF PERFORMANCE

Construction Products Regulation 305/2011

No. 1500-1603

Engineering Grade Retroreflective Sheeting:

T-1500 Series
T-1500 Series with OL-2000 Transparent EC Film
T-1500 Series with 4930 Screen Ink
T-1500 Series with UVTS Screen Ink
T-1500 Series with 3801 Black Opaque Film
T-1500 Series with TrafficJet Ink & Clear Overlay



T-1500 EG Series, in conjunction with the components listed, is a high-quality, 7-year durable, beaded retroreflective material with a pressure sensitive adhesive. This product is intended for use on permanent or temporary highway safety devices that require Class 1 retroreflective performance.



Manufactured by: Avery Dennison, Reflective Solutions

Willem Einthovenstraat 11, 2342 BH
Oegstgeest, The Netherlands

902 Feehanville Rd.
Mt. Prospect, IL 60056 USA

Avery Dennison performed factory product control and product sampling per assessment and verification of constancy of performance under System 1. Silniční vývoj - ZDZ spol. s r. o., Notified Body 1388, performed initial type testing, inspection of manufacturing facilities and factory products controls under system 1 and issued No.1388-CPR-6.2/2017

Essential Characteristics		Performance	Assessment Document
Daylight Chromaticity		CR2	EN 12899-1:2007
Luminance Factor		CR2	
Coefficient of retro-reflection		RA1	
Impact Resistance		No Effect	
Visibility after Weathering, Natural & Accelerated Artificial	Retroreflection	80% of Initial Requirement	
	Chromaticity & Luminance Factor	Per Table 2 Below	

The performance of T-1500 EG Series is in conformance with declarations herein when evaluated per EN 12899-1:2007. This declaration of performance is issued for performance clarity under the sole discretion of Avery Dennison.

Signed for on behalf of Avery Dennison by: Sandeep Kottarath, Global Quality Manager

Date: 30 October 2017, Illinois, USA

Table 2: Daytime Chromaticity and Luminance Factors^A

Colour		Colour Box Coordinates				Luminance Factor β
		1	2	3	4	
White	x	0,355	0,305	0,285	0,335	$\geq 0,27$
	y	0,355	0,305	0,325	0,375	
Yellow	x	0,545	0,487	0,427	0,465	$\geq 0,16$
	y	0,454	0,423	0,483	0,534	
Red	x	0,735	0,674	0,569	0,655	$\geq 0,03$
	y	0,265	0,236	0,341	0,345	
Orange	x	0,631	0,560	0,506	0,570	$\geq 0,14$
	y	0,369	0,360	0,404	0,429	
Green	x	0,007	0,248	0,177	0,026	$\geq 0,03$
	y	0,703	0,409	0,362	0,399	
Brown	x	0,455	0,523	0,558	0,479	$0,01 \leq \beta \leq 0,09$
	y	0,397	0,429	0,394	0,373	
Blue	x	0,078	0,150	0,210	0,137	$\geq 0,01$
	y	0,171	0,220	0,160	0,038	
Black	x	0,385	0,300	0,260	0,345	$\leq 0,03$
	y	0,355	0,270	0,310	0,395	

Notes: A – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EN 12899-1:2007, Section 4.1.1.3.

Table 3: Coefficients of Retroreflection¹, Class RA1

Entrance Angle (β_1 , $\beta_2=0^\circ$)	Observation Angle (α)	R_A						
		White	Yellow	Orange	Green	Red	Blue	Brown
5°	0.2°	70	50	25	9	14.5	4	1
30°		30	22	10	3.5	6	1.7	0.3
40°		10	7	2.2	1.5	2	0.5	-
5°	0.33°	50	35	20	7	10	2	0.6
30°		24	16	8	3	4	1	0.2
40°		9	6	2.2	1.2	1.8	-	-
5°	2.0°	5	3	1.2	0.5	1	-	-
30°		2.5	1.5	0.5	0.3	0.5	-	-
40°		1.5	1	-	0.2	0.5	-	-

Notes: 1 – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EN 12899-1:2007, Section 4.1.1.4.

Table 4: Specific Signing Combination Performance Declarations

Signing Component	Product Name	Colors and Product Number	Declared Retroreflective Detail
Native Sheeting	T-1500 Series	T-1500A* & T-1500D White* T-1501A* & T-1501D Yellow* T-1505A* Blue^ T-1507A* Green T-1508A* Red T-1509A* Brown	Per Table 3
Electronic Cuttable Overlay [#]	OL-2000 EC Film & 3801 Black	OL-2000 Clear Applied to T-1500D 3801 Black	Per Table 3
Solvent Screen Ink [#]	4930 Series	Yellow Applied to T-1500A* Blue Applied to T-1500A** Green Applied to T-1500A* Red Applied to T-1500A** Red Applied to T-1501A Yellow ⁺ , * Black Applied to T-1500A	70% of Table 3
Screen Printing [#]	UVTS Ink	Yellow Applied to T-1500 ^{d, ^} Blue Applied to T-1500 ^{d, ^} Red Applied to T-1500 ^{d, ^} Black Applied to T-1500	70% of Table 3
Digital Printing [#]	TrafficJet with OL-1000 or OL-2000 Clear	Yellow Applied to T-1500D ^d Blue Applied to T-1500D ^d Green Applied to T-1500D ^d Red Applied to T-1500D ^d Red Applied to T-1501D Yellow ⁺ Brown Applied to T-1500D ^d Black Applied to T-1500D Black Applied to T-1501D	70% of Table 3

Notes: [#] - Declared performance for components assumes application to white native sheeting unless otherwise noted.

[^] - Daytime Chromaticity does not conform to CR2 colorbox

^d - Declared performance is 100% of Table 3 values when processed per German requirements.

* - Combination for which weathering declaration is made under natural weathering protocol.

⁺ - Declared performance is 50% of red values stated in Table 3.