


DECLARATION OF PERFORMANCE

Construction Products Regulation 305/2011

No. 7000-1606

Prismatic Retroreflective Sheeting:

- T-7500MVP Series
- T-7500MVP Series with OL-2000 Transparent EC Film
- T-7500MVP Series with 4930 Screen Ink
- T-7500MVP Series with 3801 Traffic Film Black
- T-7500MVP Series with TrafficJet Ink & Clear Overlay



T-7500MVP Series is a high-quality, 10-year durable, microprismatic retroreflective material with a pressure sensitive adhesive. This product is intended for use on permanent or temporary highway safety devices that require robust Class 3 retroreflective performance.



Manufactured by: Avery Dennison, Reflective Solutions

Willem Einthovenstraat 11, 2342 BH
Oegstgeest, The Netherlands

902 Feehanville Rd.
Mt. Prospect, IL 60056 USA

Avery Dennison performed factory product control and product sampling per assessment and verification of constancy of performance under System 1. Silniční vývoj - ZDZ spol. s r. o. Notified Body 1388 performed initial type testing, inspection of manufacturing facilities and factory products controls under system 1. Tzus, 060-045345 issued **ETA 15/0889** dated 25/10/2017.

Essential Characteristics		Performance	Assessment Document
Daylight Chromaticity		Per Table 2	EAD 120001-01-0106, September 2016
Luminance Factor		Per Table 2	
Coefficient of retro-reflection, Rotational Symmetry		Per Table 3, Rotational Variation < 10%	
Impact Resistance		No Effect	
Visibility after Weathering, Natural & Accelerated Artificial	Retroreflection	80% of Initial Requirement	
	Chromaticity & Luminance Factor	Per Table 2 Below	
Adhesion		Peel < 50mm	

The performance of T-7500 MVP Series is in conformance with declarations herein when evaluated per EAD 120001-01-0106. This declaration of performance is issued for performance clarity under the sole discretion of Avery Dennison.

Signed for on behalf of Avery Dennison by: Sandeep Kottarath, Global Quality Manager

Date: 30 October 2017, Illinois, USA

Table 2: Daytime Chromaticity and Luminance Factors^A

Colour		Colour Box Coordinates				Luminance Factor β
		1	2	3	4	
White	x	0,355	0,305	0,285	0,335	$\geq 0,27$
	y	0,355	0,305	0,325	0,375	
Yellow	x	0,545	0,487	0,427	0,465	$\geq 0,16$
	y	0,454	0,423	0,483	0,534	
Red	x	0,735	0,674	0,569	0,655	$\geq 0,03$
	y	0,265	0,236	0,341	0,345	
Green	x	0,007	0,248	0,177	0,026	$\geq 0,03$
	y	0,703	0,409	0,362	0,399	
Brown	x	0,455	0,523	0,558	0,479	$0,01 \leq \beta \leq 0,09$
	y	0,397	0,429	0,394	0,373	
Blue	x	0,078	0,150	0,210	0,137	$\geq 0,01$
	y	0,171	0,220	0,160	0,038	
Black	x	0,385	0,300	0,260	0,345	$\leq 0,03$
	y	0,355	0,270	0,310	0,395	

Notes: ^A – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.1.

Table 3: Coefficients of Retroreflection¹, R_A (cd/lux/m²)
(Includes DIN 3A, GRE 3A, Spain 3ZA Requirements)

Entrance Angle (β_1 , $\beta_2=0^\circ$)	Observation Angle (α)	R_A					
		White	Yellow	Orange	Green	Red	Blue
5°	0.1°	900	720	450	90	250	55
20°		600	390	300	60	120	40
30°		495	405	315	45	135	28
40°		340	270	180	27	85	18
5°	0.2°	720	600	360	75	195	40
20°		450	290	225	45	90	30
30°		360	310	225	30	90	20
40°		200	155	70	20	45	13
5°	0.33°	425	275	210	40	85	28
20°		300	195	150	30	60	20
30°		225	145	110	20	45	15
40°		150	95	75	15	30	10
5°	0.5°	180	140	110	18	40	9
30°		90	75	50	9	23	4
40°		70	55	40	5	16	2.5

Notes: ¹ – When material is sampled, processed and tested per Avery Dennison Product Data Bulletins, Instructional Bulletins, and EAD 120001-01-0106, Section 2.2.3 at $\epsilon=0^\circ$ only.

Table 4: Specific Signing Combination Performance Declarations

Signing Component	Product Name	Colors and Product Number	Declared Retroreflective Detail
Native Sheeting	T-7500 MVP Series	T-7500 MVP White T-7501 MVP Yellow T-7505 MVP Blue T-7507 MVP Green T-7508 MVP Red T-7511MVP Fluorescent Yellow T-7513MVP Fluorescent Yellow-Green	Per Table 3
Electronic Cuttable Overlay [#]	OL-2000 EC Film & 3801 Black	OL-2000 Clear OL-2001 Yellow OL-2005 Blue OL-2007 Green OL-2008 Red 3801 Black	70% of Table 3
Solvent Screen Ink [#]	4930 Series	Blue Red Black	70% of Table 3
Digital Printing [#]	TrafficJet with OL-1000 or OL-2000 Clear	Yellow Blue Green Red Red Applied to T-7501 MVP Yellow Brown Black	70% of Table 3

Notes: [#] - Declared performance for components assumes application to white native sheeting unless otherwise noted.

* - Declared performance is 50% of red values stated in Table 3.