

Avery Dennison®

VisiFlex™ V-8000 Application Guidelines

Instructional Bulletin : # 8.17
Revision : # 01
Last Updated : December 2017

Storage conditions

Avery Dennison® VisiFlex™ V-8000 can be stored at temperatures of 18-24°C (64-75°F) and a relative humidity of 45-55%.

Application Conditions

Ideal conditions for application are between 15-38°C (60-100°F).

Surface Preparation

The use of Avery Dennison® Surface Cleaner is recommended to clean the surface before fitting.

Application Steps

1. Put your first panel in place
Suggestions:
 - Start with the handles
 - Use magnets as they allow you to line the material up before taping a hinge into place
2. Hinge the material
3. Remove backing linear and run your thumb over the hinged piece of material
4. Once happy with overall positioning, squeegee material onto the vehicle – work from side to side applying pressure to remove air bubbles
 - 4a. If unhappy with alignment carefully peel the panel back and re-position
5. If a panel is attached to previously fitted panel start this one from the joint
6. Always firmly squeegee the material into the curves to ensure a strong adhesion
7. Slightly warm up the edges and run over it once more with the squeegee or glove

IMPORTANT

- Do NOT use water or other application fluid!
- When tiling vertically, always make sure the wind from driving forwards is not blowing into your overlap
- Because of the Solid Metallic Layer construction, edge sealing is not required

TIP

Use a blue Avery Dennison® squeegee with a felt edge to prevent scratches

The above Avery Dennison literature provides information to the user for proper application, storage and other requirements. Please refer to Product Data Bulletins or your local Avery Dennison Representative for warranty information. Find the latest information on the Avery Dennison website, www.reflectives.averydennison.com. We encourage you to check our website periodically for updates.

All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable, but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that Purchaser has independently determined the suitability of such products for its intended and other purposes.

For technical questions, please contact:

North America: reflective.tech.na@averydennison.com

Europe, Middle East & Africa: reflective.tech.eu@eu.averydennison.com

Asia Pacific: reflective.tech.ap@ap.averydennison.com

South America: reflective.tech.sa@averydennison.com