



TrafficJet™ With CMSpot6™



Simple, Clean, Cost-effective

- » The revolutionary TrafficJet™ Print System is based on the Mutoh ValueJet printer platform and uses TrafficJet™ CMSpot6™ eco-solvent inks.
- » Traffic signs and images produced with TrafficJet™ according to Avery Dennison recommendations (including the use of a protective overlay film) are warranted up to 12 years. Refer to individual sheeting series Product Data Bulletins for complete details.
- » Construction work zone signs produced with TrafficJet™ TJ03 Black are warranted for 3 years without a protective overlay film.
- » Insist on a printer that provides specification compliance and long-term warranted durability. Every TrafficJet™ Print System includes the printer, expert on-site installation, print calibration, operator training, and 1 year warranty.

TrafficJet™ 1638X Specifications

Print method	Drop-On-Demand, Piezo Drive Method	Maximum media roll weight	29,93 kg
# of nozzles	(180 x 8 rows) x 2 staggered heads	Media roll diameter / Core	15,24 cm maximum / Cores 7,62 cm or 5,08 cm
Ink type	TrafficJet™ Eco-Solvent Spot Colors & Mutoh Eco-Ultra Ink (CMYK)	Take-up system	Standard
Variable dot	Yes	Media auto cut	Standard
Minimum droplet size	3,5 pl	RIP Software	FlexiSIGN & Print
Print modes	1440/720/540/360 dpi 10 + modes	Power requirements	220-230V / 20AMP
Color options	CMSpot6	Operating temperature	20°C – 32°C
Number of print heads	2	Operating humidity range	40% – 60%
Maximum print speed / resolution	94 sqm/hr	Dimensions (printer) WxDxH	269,24 x 88,9 x 127 cm
Maximum resolution	1440 dpi	Dimensions (shipping info)	289,56 x 116,84 x 129,54 cm
Traffic sign print speed	8,1 m²/hr	Weight (printer)	Printer 184,61 kg / Stand 34,02 kg
Head Height	Low: 1.5mm / Medium 2.5mm / High 4.0mm	Weight (shipping info)	330,22 kg
Maximum media width	162,56 cm	Limited warranty	1 year
Maximum print width	161,54 cm		



Inspired Brands.
Intelligent World.™

Avery Dennison Reflective Europe
Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
Phone: +31 (0)85 000 2415
Fax: +31 (0)71 342 1396

©2017 The Avery Dennison Corporation. All Rights Reserved.
Avery Dennison and all Avery Dennison product codes are
trademarks of Avery Dennison Corporation

S-92282